# Hydrogen sulphide

Marking

CAS

Characterization acc. ADR

7783-06-4 UN 1053 HYDROGEN SULPHIDE, 2.3 (2.1), (B/D), ENVIRONMENTALLYHAZARDO US

Cylinder Marking

Shoulder color: yellow

## **Essential properties**

liquified gas, heavier than air, colorless, smelling like rotten eggs, flammable, irritant, toxic, toxic to aquatic life

### Symbols of risks











## **Physical Properties**

molecular weight 34,076 kg/kmol gas density at 0°C and 1,013 bar 1,5359 kg/m³ density ratio to air 1,1879 vapour pressure at 20°C 18,190 bar

For additional safety information see safety data sheet \*-H2S-073

Valves / Manifolds

Valve connection acc. to national regulations

Recommended Manifolds Spectrocem FE121SP



Specification / receptacles				
		Hydrogen sulphide 2.5		
Composition				
H₂S	≥	99.5	Vol%	
Impurities				
cos	<	3,000	ppmv	
CH₄	<	500	ppmv	

#### Remarks

Delivery only with end user statement! No delivery to private person!

# Hydrogen sulphide

Marking

CAS

Characterization acc. ADR

7783-06-4 UN 1053 HYDROGEN SULPHIDE, 2.3 (2.1), (B/D), ENVIRONMENTALLYHAZARDO US

Cylinder Marking

Shoulder color: yellow

## **Essential properties**

liquified gas, heavier than air, colorless, smelling like rotten eggs, flammable, irritant, toxic, toxic to aquatic life

#### Symbols of risks



For additional safety information see safety data sheet \*-H2S-073

## **Description**

Colourless, highly flammable, toxic, in presence of moisture corrosive, liquified gas with characteristic odor like rotten eggs. In high concentrations the olfactory nerves are stunned, so the warning effect is dropped. Strong reducing agent, possible reaction up to ignition with oxidizers. Acc. to ISO 10298: LC50/1h = 712 ppm.

### **Materials**

Cylinders and valves: any usual materials.

Normalized / annealed steel only under observance of the required max. strength properties; danger of hydrogen embrittling. Seals: PTFE, PCTFE, PVDF, PA, PE.

Physical Properties			
molecular weight	34,076 kg/kmol	vapour pressure at 20°C	18,190 bar
critical point		gas density at 0°C and 1,013 bar	1,5359 kg/m³
temperature	373,2 K	density ratio to air	1,1879
Pressure	89,4 bar	gas density at 15°C and 1 bar	1,435 kg/m³
density	0,346 kg/l	conversion factor	
triple point		liquid at Ts to m³ gas (15°C, 1 bar)	1,568
temperature	187,5 K	virial coefficient	
Pressure	0,227 bar	Bn at 0°C	-10,0*10 <sup>-3</sup> bar <sup>-1</sup>
boiling point		B30 at 30°C	-7,0*10 <sup>-3</sup> bar <sup>-1</sup>
temperature	213,0 K; -60,2 °C	gaseous state at 25°C and 1 bar	
liquid density	0,9149 kg/l	specific heat capacity cp	1,0042 kJ/kg K
evaporation heat	548 kJ/kg	thermal conductivity	143*10⁻⁴ W/m K
		dynam. viscosity	1,286*10 <sup>-5</sup> Ns/m <sup>2</sup>